

*radius**angle**round**bullnose*

# B

## E. R. BUTLER & CO.

### *Concealed Edge Pulls (Jib)*

“JIB PULLS,” as they are commonly known, are concealed edge pulls traditionally installed on “jib doors”: doors flush with a wall surface, and decorated only with whatever dressings occur in the room upon it, such as base or chair rail mouldings or wainscoting. Their uses are not limited to concealed doors; they may also be installed horizontally or vertically on drawers as well as on doors. E.R. Butler & Co. offers jib pulls in four profiles: radius, angle, round and bullnose. Jib pulls are

available in two standard widths, 1¾ and 2¼ inches, to accommodate varying door thicknesses. Standard lengths for jib pulls are 1, 1½, 2, 2½, 3, 3½, 4, 4½, 5, 6, 8, and 10 inches. They are also available by special order in lengths up to 12 feet. To provide for superior strength and durability, E.R. Butler & Co. manufactures jib pulls from 3/16 inch thick extruded solid brass. Concealed edge pulls are available in all standard, custom plated and patinated finishes.

WWW.ERBUTLER.COM

CATALOGUES AVAILABLE TO THE TRADE · SHOWROOMS BY APPOINTMENT ONLY

FINE ARCHITECTURAL, BUILDERS' AND CABINETMAKERS' HARDWARE